

This kit provides complete arc flash and shock protection for electric vehicle (EV) hazards up to 8 cal/cm² or Category 2 arc flash hazards and up to 1,500 VDC shock hazards.

A special all-in-one solution — made to order based on body size for the coverall and hand size for the gloves, making it just right for you.





OBERON ELECTRIC VEHICLE (EV) ARC FLASH & SHOCK KIT

Coverall, BSA-CBX7NB-ES-(size):

- Designed without pockets or openings for maximum incident prevention and worker protection
- Includes a rescue escape strap used for emergency response and contact release that extends from the back of the garment, replacing the need for a rescue stick
- 8 cal/cm² ATPV Coveralls, Navy Blue, made with 7 oz/yd², 88% cotton/12% nylon flame-resistant treated fabric
- Coveralls available in regular, tall, and short sizes
- Standard regular sizes are RS, RM, RL, RXL, R2XL, R3XL, R4XL, and R5XL.
 Refer to Oberon sizing chart for guidance on selection
- CSA Z462/NFPA 70E Complaint
- ASTM F1506
- ANSI/ISEA 125 Level 2 Conformity

Face Shield 21AGR12AF-A5+500:

- 17 cal/cm² AR_{Lim} Face shield, constructed with True Color Grey (TCG) polycarbonate lens technology
- CSA Z462/NFPA 70E Complaint
- ASTM F2178
- ANSI Z87+ High Impact
- ANSI/ISEA 125 Level 2 Conformity

Hard Hat HC6P-RED-4:

- · Arc-flash tested with Oberon face shield
- Includes ratchet suspension
- CSA Z462/NFPA 70E Complaint
- ANSI Z89.1/CSA Z94.1 Type 1, Class C, G, and E
- ANSI/ISEA 125 Level 2 Conformity

Balaclava, CAT11-BH-GR-LG:

- To be worn with a face shield and hard hat to provide complete 360° face and head protection
- 11 cal/cm² ATPV Balaclava, Grey, made with 6.3 oz/yd², 100% cotton flame-resistant treated fabric
- CSA Z462/NFPA 70E Complaint
- ASTM F1506
- ANSI/ISEA 125 Level 2 Conformity



Class 0 Glove Kit, GLVKT-BRCO-(size):

- Class 0 Rubber Insulating Gloves, Black, rated for voltages up to 1,000 VAC or 1,500 VDC
- Class 0 Leather Glove protectors
- Canvas Storage Bag
- Gloves available in size 07, 08, 09, 10, 11, or 12.
- Refer to Oberon sizing chart for guidance on selection
- CSA Z462/NFPA 70E Complaint
- ASTM D120
- ASTM F696



sellstrom.

Sellstrom Safety Glasses, S70701:

- Lightweight, comfortable and very affordable
- Lens features an anti-scratch hard coating
- CSA Z94.3
- ANSI Z87.1



sellstrom .

Sellstrom Ear Plugs, S23410:

- Contoured bullet shape premium-quality polyurethane ear plugs
- Gently but quickly expand to fit ear canal

 one size fits all!
- NRR 32
- CSA Class AL, Z94.2
- ANSI S3.19



